

		<p>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading an ISO CONTAINER at a LyondellBasell site or a contracted 3PL location as applicable</p>
ISO CONTAINER SPECIFICATION		
PRODUCT	WFE B DISTILLATE	WFE - B
Material Characteristic and immediate hazard		See Product SDS
DOT SPECIFICATION	<p>IM 101, UN T-11, MAX. - 24K LITERS/LITRES, (STAINLESS STEEL ISO CONTAINER). CONTAINER MUST BE APPROVED AND DESIGNATED BY LYB TO TRANSPORT WFE B DISTILLATE. DEDICATED CONTAINER IS NOT REQUIRED, BUT DEDICATED SERVICES CONTAINER WILL REQUIRE LYB WRITTEN PRE-APPROVAL PRIOR TO LOADING OR TRANSPORT OF WFE B DISTILLATE. SPECIAL NOTE: DATA PLATE INFORMATION MUST BE LEGIBLE AND CORRECTLY STAMPED. INSPECTION DOCUMENTATION MUST BE WITH DRIVER AS ADDITIONAL PROOF OF INSPECTION/TEST DATE VERIFICATION, TO HELP PREVENT EQUIPMENT REJECTION.</p>	
INSULATION	REQUIRED	
HEATING CAPABILITIES	REQUIRED	
GASKET MATERIAL	VIRGIN TEFLON, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A LEAK TIGHT SEAL UPON COMPLETION OF LOADING	
CONNECTIONS/FITTINGS	ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL.	
LIQUID CONNECTION	<p>EXPORT SHIPMENT: BLIND FLANGE ON BOTTOM OUTLET IF CONTAINER IS TO BE LOADED ON RAIL OR VESSEL; BOTTOM OUTLET MUST HAVE A SOLID CLOSURE; DUST CAPS NOT ACCEPTABLE. DOMESTIC SHIPMENT: A FLANGED 3" MALE CAMLOCK (QUICK CONNECT) W/DUST CAP - BOTTOM REAR LOADER . BOTH SHIPMENT TYPES MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL.</p>	
VAPOR CONNECTION	<p>1 1/2 INCH BALL VALVE WITH BULL PLUG, BULL PLUG MUST BE ATTACHED WITH CHAIN/CABLE AND VALVE MUST BE ABLE TO SEALED W/1/8" WIRE CABLE SEAL. NOTE: PROTECTIVE COVER FOR MAN-LID AND VAPOR CONNECTION MUST ALSO HAVE THE CAPABILITY TO SEALED. THIS APPLIES FOR EXPORT OR DOMESTIC SHIPMENTS</p>	
NITROGEN PADDING	<p>NITROGEN PURGE FOR DRYING & MOISTURE CONTROL. CLEAN ISO CONTAINER MUST HAVE A 5-7 PSIG PAD UPON ARRIVAL AT LOADING FACILITY. RE-LOAD/RESUE CONTAINER MAY RETURN WITH LAST OFF-LOADING PRESSURE OR MINIMUM OF 5-7 PSIG.</p>	
TANK CLEANLINESS	<p>IF CONTAINER IS CLEANED, A CLEANING CERTIFICATE IS REQUIRED. CONTAINER MUST BE CLEAN, DRY, AND ODOR FREE. NOTE: IF ISO CONTAINER IS RE-LOAD, THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF THAT LAST CONTAINED WAS LYONDELLBASELL MATERIAL.</p>	
STRAPPING CHART REQUIRED	YES, NOTE: LEVEL GAUGE/INDICATOR ALSO PREFERRED	
HOSES	HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. NOTE: HOSE(S) ARE NOT TRANSPORTED BY CARRIER FOR EXPORT SHIPMENTS.	
ADDITIONAL APPURTENANCES OR REQUIREMENTS	<p>NONE - NOTE: CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENING TO ISO CONTAINER MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL. NOTE: PRODUCT LABELING IS REQUIRED WITH CONTAINER/(DRIVER), UPON ARRIVAL TO LOADING FACILITY. DRIVER MUST ENSURE PRODUCT NAME/LABELING IS APPLIED TO BOTH SIDE OF THE CONTAINER PRIOR TO LEAVING THE LOADING FACILITY.</p>	
OTHER	<p>MUST HAVE LYB CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELL OF ANY REQUESTED LIGHT LOADING, (PRIOR TO LOADING), DUE TO POTENTIAL EXCEEDING LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS</p>	
PROHIBITED	PETS ARE PROHIBITED; ADDITIONAL PERSONNEL ONLY IF TEAM DRIVERS	